



LAMPADE FLUORESCENTI FLUORESCENT LAMPS

Altri tipi - Other Types

T8 (Ø 26 mm) - Attacco bispina normale G13 / T8 (Ø 26 mm) - Standard G13 double-pin base



Codice Code	Type	W	lm	L mm			Cod. EAN 8009935...	
400371.0101	14-16 T8/CW	14-16W	750	361	25	3000	044594	
400375.0101	14-16 T8/D	14-16W	700	361	25	3000	044662	
400721.0101	15 T8/CW	15W	870	437	25	3000	044310	
400901.0101	15 T8/D	15W	750	437	25	3000	044327	
401771.0101	23 T8/CW	23W	1900	970	25	1000	044730	
401781.0101	23 T8/D	23W	1500	970	25	1000	044808	
401801.0101	30 T8/CW	30W	2200	895	25	1000	044877	
401981.0101	30 T8/D	30W	1900	895	25	1000	044945	

Circolari 2GX13 - Circular 2GX13

Codice Code	Type	W	lm	L mm		Cod. EAN 8009935...	
415125.0101	FC5/827	22W-T5	1800	225	12	043733	NEW
415126.0101	FC5/827	40W-T5	3200	300	12	043801	NEW
415127.0101	FC5/827	55W-T5	4200	300	12	043870	NEW

2700 K

415122.0101	FC5/840	22W-T5	1800	225	12	043337	
415123.0101	FC5/840	40W-T5	3200	300	12	043405	
415124.0101	FC5/840	55W-T5	4200	300	12	043191	

4000 K

Circolari G10q trifosforo - Triphosphor circular G10q

Codice Code	Type	W	lm	Ø D mm		Cod. EAN 8009935...	
492256.0101	T9/827	22W	1250	216	12	062185	NEW
492257.0101	T9/840	22W	1250	216	12	062253	NEW
492277.0101	T9/865	22W	1250	216	12	062543	NEW
492258.0101	T9/827	32W	2100	311	12	062321	NEW
492259.0101	T9/840	32W	2100	311	12	062390	NEW
492278.0101	T9/865	32W	2100	311	12	062611	NEW
492260.0101	T9/827	40W	2800	413	12	062468	NEW
492261.0101	T9/840	40W	2800	413	12	062536	NEW
492279.0101	T9/865	40W	2800	413	12	062680	NEW

Circolari G10q - Circular G10q

● 415121.0101	FC8/CW	22W	950	216	12	043474	
● 415301.0101	FC8/D	22W	950	216	12	043610	
● 415391.0101	FC12/CW	32W	1700	311	12	043481	
● 415571.0101	FC12/D	32W	1700	311	12	043627	
● 415661.0101	FC16/CW	40W	2250	413	12	043498	
● 415841.0101	FC16/D	40W	2250	413	12	043634	

Starter Convenzionale

Codice Code	Type	Per Lampada For Lamp		
S53991 *	FS-2	4÷22W	25	B
S53993	St U	4÷80W	25	A

*Particolarmente indicato per applicazioni in serie (110V)
* Especially indicated for applications in series (110V)

Starter Convenzionale

S53986	EOS 18÷80	18÷80W 300 mA	40	A
--------	-----------	---------------	----	----------

Schema di collegamento
Diagram suitable

