

COMPATTE BASSA PRESSIONE - LOW PRESSURE COMPACT - 3.000 H

Filamento assiale chiara - Axial filament clear



Codice Code	V	W		Ø D mm	L mm	lm		Cod. EAN 8009935...
094420.0101	12	5	G4	9	33	60	40	346841
094471.0101	12	10	G4	9	33	130	50	346001
094473.0101	12	20	G4	9	33	320	50	346018
094493.0101	12	20	GY 6.35	12	44	320	50	346049
094474.0101	12	35	G4	9	33	600	50	346025
094494.0101	12	35	GY 6.35	12	44	600	50	346056
094495.0101	12	50	GY 6.35	12	44	900	50	346063
094444.0101	12	75	GY6.35	12	44	1450	50	347718

3000 K

Filamento assiale smerigliata - Axial filament frosted



Codice Code	V	W		Ø D mm	L mm	lm		Cod. EAN 8009935...
094470.0101	12	10	G4	9	33	130	50	346070
094472.0101	12	20	G4	9	33	300	50	346087
094477.0101	12	20	GY 6.35	12	44	300	50	346117
094521.0101	12	35	GY 6.35	12	44	600	50	346124
094522.0101	12	50	GY 6.35	12	44	900	50	346131

3000 K

Forni 300° - Filamento assiale - chiara - Oven 300° Axial filament - clear



Codice Code	V	W		Ø D mm	L mm	lm		Cod. EAN 8009935...
094455.0101	12	10	G4	9	33	130	50	346254
094457.0101	12	20	G4	9	33	320	50	346261

3000 K

Filamento assiale - chiara - Axial filament clear



Codice Code	V	W		Ø D mm	L mm	lm		Cod. EAN 8009935...
094446.0101*	24	20	G4	9	33	320	40	347701
094447.0101	24	50	GY6.35	12	44	850	40	347725

* filamento orizzontale / horizontal filament

3000 K